# TP-LINK®

## Wireless N ADSL2+ Modem Router

## **TD-W8960N**



3-in-1: ADSL2+ modem, 4-port Ethernet router and wireless N access point 300Mbps wireless transmission rate, brings smooth wireless N experience Various QoS policies enable various application, meeting people's different needs







# **Description:**

The TD-W8960N Wireless N ADSL2+ Modem Router is an All-in-One device that combines the functions of a high speed DSL modem, a 4-Port 10/100Mbps NAT router and a wireless access point. It is designed to give you a one-stop solution to acquire and share high speed Internet access over a wired/wireless network. Supporting the latest ADSL standards, the TD-W8960N brings with it much higher speed than a dial-up connection without tying up the phone line. Compling with the IEEE 802.11n, users will get

up to 15X the speed and 5X the range of conventional 11g products. Now you can enjoy more kinds of bandwidth consuming applications like HD video streaming wirelessly which can not be accommodated by 11g products, from anywhere in your entire home or even the yard. In addition, with the function of IPSec VPN (site-to-site), TD-W8960N can guarantee the security of the data transmition from home to corporate network or between remote branch offices.

#### Specifications:

Interfaces	1 RJ11 port, 4 Ethernet ports, support IEEE802.3,802.3u
Data Rates	Downstream: Up to 24Mbps
	Upstream: Up to 3.5Mbps(With Annex M enabled) Full-rate ANSI T1.413 Issue 2
ADSL Features  ATM Features	ITU-T G.992.1 (G.dmt)
	ITU-T G.992.1 (G.Giite)
	ITU-T G.994.1 (G.hs)
	ITU-T G.992.3 (G.dmt.bis)
	ITU-T G.992.5 (G.GHIT.BIS)
	Supports Annex A/L/M
	Max 6 kilometers
	UNI 3.1, ATM Adaptation Layer Type 5-AAL5
	Multiprotocol encapsulation over ATM (RFC 1483)
	UBR, CBR, VBR-rt, VBR-nrt
	Supports 8PVCs
	PPP over ATM (RFC 2364)
PPP Features	PPP over Ethernet (RFC 2516)
	IGMP snooping
Switching Features	IGMP multicast
	IEEE 802.1d transparent learning bridging
Routing Features	Clasical IP and ARP over ATM (RFC 1577/2225), RIP V1/V2
	MAC Encapsulation Routing
	Static routing, IP, TCP, UDP, ARP
	NAT, NAPT, DNS, DDNS, DHCP Server
	UPnP, Virtual Server, DMZ, Port Trigger
	SIP, H323 ALG
Wireless Features	Complies with IEEE 802.11n ,IEEE 802.11g, IEEE802.11b
	Wireless speed up to 300M
	Provides WPA/WPA2 and WPA-PSK/WPA2-PSK authentication and
	TKIP/AES encryption security
	Provides 64/128-bit WEP encryption security and wireless LAN AC
	(Access Control List)
	Max wireless transmit power: 19dbm
	Antenna power: 3dbi
Security	NAT and SPI Firewall, Packet Filter
VPN	Support up to 10 IPSec VPN tunnels
VPN Pass Through	IPSec/PPTP/L2TP Pass-through
QoS	IP Type of service(ToS)
	802.1p
	HTTP, Console
Device Management	Administration and operation software (firmware) upgradable
	locally by web(HTTP), console(TFTP)
Lod	CWMP(TR-069) Power, Internet, ADSL, WLAN, LAN1~4,QSS
Led Operating Temperature	0°C~40°C (32°F~104°F)
Storage Temperature	-40°C~70°C (-40°F~158°F)
Operating Humidity	10% ~ 90%, non condensation
Storage Humidity	5%~90% non-condensing
Dimensions(L x W x H)	7.9 x 5.5 x 1.1 in.(200 x 140 x 28mm)
Z.IIICIISIOIIS(EAWAII)	

#### Features:

- High speed DSL modem, NAT router and wireless access point in one device provides one-stop networking solution
- Wireless N speed up to 300Mbps makes it ideal for bandwidth consuming or interruption sensitive applications like video streaming, online gaming and VoIP
- 2T2R MIMO technology provides robust high-bandwidth wireless Tx/Rx capability at further range
- Support Annex M, which can double upstream data rates
- Support up to 10 IPSec VPN tunnels simultaneously, offering you the most economic way to connect to the company's central network securely
- Easy Setup Assistant provides quick & hassle free installation
- Easily setup a WPA encrypted secure connection at a push of the QSS button
- Dual Firewall (NAT and SPI firewall) protects LAN devices from potential attacks from across the Internet
- QoS enables smooth VoIP/IPTV streaming and lag-free online gaming
- Auto-reconnect keeps you online indefinitely
- Port-mapping binds specific LAN ports and PVCs for differential services
- TR-069 enables centralized management

## Package:

- Wireless N ADSL2+ Modem Router TD-W8960N
- One DC power Adapter
- Quick Installation Guide
- One RJ45 cable
- Two RJ11 cables
- One ADSL splitter
- One Resource CD

#### **Related Products:**

- 300M Wireless Cardbus Adapter TL-W811N
- 300M Wireless USB Adapter TL-WN821N
- 300M Wireless PCI Adapter TL-WN851N

### Diagram:

